


- ★ Robust Polycarbonate & ABS body with Color Changeable Technology
- ★ No mercury or other hazardous materials
- ★ Built with Quality Driver and 2835LED Chip
- ★ 30,000 hours life with 3 years warranty
- ★ Emergency version available
- ★ Can be wall mounted and ceiling mounted
- ★ PC Lens with high lumen output
- ★ IP65 & IK08 with white finish



## MIRAGE

Applications: Indoor & Outdoor

### Specifications



Replaces		
Part Code	BMIFITWHIWALL/CEILTR	BMIFITWHIWALL/CEILEM
Trade Price		

Luminescence	Light colour	3000K / 4000K / 6500K	3000K / 4000K / 6500K
	Ra, Consistency		
	Luminous flux	1,600lm	1,600lm
	Beam angle, light intensity	120 Degree	120 Degree
	Accent Lighting	Yes	Yes
	Warm up time	Instant	Instant
	Dimmable	No	No

Technical	Power input (50-60Hz AC)		
	Power factor & Current	>0.9	>0.9
	Lamp type	2835	2835
	Fire rated	No	No
	Working temperature	-25-40 C	-25-40 C
	Construction	PC & ABS	PC & ABS
	IP & IK rating	IP65 & IK08	IP65 & IK08

Efficiency	Energy Efficiency Label	A+	A+
	EC(Energy consumption)	18KWH/1000H	18KWH/1000H
	Lifetime	30000H	30000H
	Building Regs - Part L	Yes	Yes
	Warranty & LMF at EoL	3 Years, 50%	3 Years, 50%
	Switching cycles	10,000X	10,000X

This document is not contractual and the equipment specification may be modified at any time without prior notice.

