

Integrated LED Emergency Downlight

- ★ Cost effective
- ★ 30,000 hours lifespan with 3 years warranty
- ★ Visible at long distance
- ★ Quality driver and battery
- ★ Uniform and High lumen output
- ★ Easy installation



General Specification		PART No BSTALONEEM	
Product Dimension	60*60*26mm	Version	Non-Maintained
Finish/Color	White	Packing Method	Color box
IP Rating	IP20	Energy Rating	A++
Dimmable (Yes/No)	No	Warranty	3 years
Light Source Specification		Electrical Specification	
CCT (K)	6500K	Input Voltage	180-240V AC 50/60Hz
Lumens Per Watt	80	Power	2W
Lumen output	160	Battery	LiFePO4
CRI (Ra)	80	Emergency time	3-4 hours
Lifetime	30000hrs	Elec. Classification	Class II
Beam Angle	120°	Control gear spec	Constant current
SMD quantity	1 pc		
Packing Specification			
Box Dimensions	225x75x60mm	Carton Dimensions	46.5X32X32cm
QTY/CTN	40	Weight	28kg
Installation			
Fixing Method	Recessed mounting	Ambient Temp	0 °C - 30 °C

This document is not contractual and the equipment specification may be modified at any time without prior notice.

