

# LED Emergency Exit Box

- ★ Cost effective
- ★ 30,000 hours lifespan with 3 years warranty
- ★ Visible at long distance
- ★ Quality driver and battery
- ★ Different direction arrows
- ★ Easy installation



| General Specification      |                 | BEXBOXLED                |                     |
|----------------------------|-----------------|--------------------------|---------------------|
| Product Dimension          | 300x192x40mm    | Version                  | Maintained          |
| Finish/Color               | White           | Packing Method           | Color box           |
| IP Rating                  | IP20            | Energy Rating            | A++                 |
| Dimmable (Yes/No)          | No              | Warranty                 | 3 years             |
| Light Source Specification |                 | Electrical Specification |                     |
| CCT (K)                    | 6500K           | Input Voltage            | 180-240V AC 50/60Hz |
| Lumens Per Watt            | 20              | Power                    | 4W                  |
| Lumen output               | 80              | Battery                  | LiFePO4             |
| CRI (Ra)                   | 80              | Emergency time           | 3-4 hours           |
| Lifetime                   | 30000hrs        | Elec. Classification     | Class I             |
| Beam Angle                 | 120°            | Control gear spec        | Constant current    |
| SMD quantity               | 18 pcs          |                          |                     |
| Packing Specification      |                 |                          |                     |
| Box Dimensions             | 195x47x310mm    | Carton Dimensions        | 50X32X40.5cm        |
| QTY/CTN                    | 20              | Weight                   | 20kg                |
| Installation               |                 |                          |                     |
| Fixing Method              | Surface mounted | Ambient Temp             | 0 °C - 30 °C        |

This document is not contractual and the equipment specification may be modified at any time without prior notice.

