

- ★ Robust Polycarbonate body with uniform light distribution
- ★ No mercury or other hazardous materials
- ★ Built with Quality Driver and 2835 LED Chip
- ★ 50,000 hours life with 5 years warranty
- ★ Emergency version available
- ★ Can be wall mounted and ceiling mounted
- ★ PC Lens with high lumen output
- ★ IP65 & IK08



PHOTON

Applications: Indoor & Outdoor

Specifications



	Standard	Emergency
Replaces		
Part Code	BPH5FTNONCOR60WFIT	BPH5FTNONCOR60WFITEM
Trade Price		

Luminescence	Light colour	5000K	5000K
	Ra, Consistency	>80	>80
	Luminous flux	6,000lm	6,000lm
	Beam angle, light intensity	120 Degree	120 Degree
	Accent Lighting	Yes	Yes
	Warm up time	Instant	Instant
	Dimmable	No	No

Technical	Power input (50-60Hz AC)	200-240V	200-240V
	Power factor & Current	>0.9	>0.9
	Lamp type	2835	2835
	Fire rated	No	No
	Working temperature	-25-40 C	-25-40 C
	Construction	Polycarbonate	Polycarbonate
	IP & IK rating	IP65 & IK08	IP65 & IK08

Efficiency	Energy Efficiency Label	A++	A++
	EC(Energy consumption)	60KWH/1000H	60KWH/1000H
	Lifetime	50,000H	50,000H
	Building Regs - Part L	Yes	Yes
	Warranty & LMF at EoL	5 Years, 50%	5 Years, 50%
	Switching cycles	10,000X	10,000X

This document is not contractual and the equipment specification may be modified at any time without prior notice.

