

AMBIENT

- ★ Cost effective
- ★ 20,000 hours lifespan with 3 years warranty
- ★ Integrated Downlight
- ★ CCT Color Changing
- ★ IP54 Water-proof
- ★ Trailing Edge Dimmable
- ★ White bezel



	Part Code	BAMBTRIDIMDL6W	BAMBTRIDIMDL8W	BAMBTRIDIMDL20W
	Trade Price	Cut-Out 70mm	Cut-Out 90mm	Cut-Out 150mm
Luminescence	Light colour	3000K/4000K/6000K	3000K/4000K/6000K	3000K/4000K/6000K
	Ra, Consistency			
	Luminous flux	500-550Lm	730-800Lm	1400-1600Lm
	Beam angle, light intensity	90 Degree	90 Degree	90 Degree
	Accent Lighting	Yes	Yes	Yes
	Warm up time	Instant	Instant	Instant
	Dimmable	Yes	Yes	Yes
Technical	Power input (50-60Hz AC)	200-240V	200-240V	200-240V
	Power factor & Current	>0.8	>0.8	>0.8
	Lamp type	SMD	SMD	SMD
	Fire rated	No	No	No
	Working temperature	-30-50 C	-30-50 C	-30-50 C
	Construction	Aluminum Plastic	Aluminum Plastic	Aluminum Plastic
	IP rating	IP54	IP54	IP54
Efficiency	Energy Efficiency Label	A+		
	EC(Energy consumption)	6KWH/1000H	8KWH/1000H	20KWH/1000H
	Lifetime	20000H	20000H	20000H
	Building Regs - Part L	Yes	Yes	Yes
	Warranty & LMF at EoL	3 Years,50%	3 Years,50%	3 Years,50%
	Switching cycles	100,000X	100,000X	100,000X

