

- ★ Robust Steel body with Color Changeable Technology
- ★ No mercury or other hazardous materials
- ★ Built with Quality Driver and 2835 LED Chips
- ★ 50,000 hours life with 5 years warranty
- ★ Emergency backup available
- ★ Can be recessed and ceiling mounted
- ★ TPA PC diffuser




UGR19 Low Glare

25w / 36w

ARC

Applications: Indoor



Specifications:

	Replaces	
	Part Code	BARCBL6X6MW
	Trade Price	
Luminescence	Light colour	3000K / 4000K / 6500K
	Ra, Consistency	> 80
	Luminous flux	3,600lm
	Beam angle, light intensity	120 Degree
	Accent Lighting	Yes
	Warm up time	Instant
	Dimmable	No
	Wattage	25W/36W
Technical	Power input (50-60Hz AC)	200 - 240 Vac
	Power factor & Current	> 0.9
	Lamp type	2835
	Fire rated	No
	Working temperature	-25-40 C
	Construction	PC TPA & Steel
	IP rating	IP20
Efficiency	Energy Efficiency Label	A+
	EC(Energy consumption)	36w
	Lifetime	50,000H
	Building Regs - Part L	Yes
	Warranty & LMF at EoL	5 Years, 50%
	Switching cycles	25,000X

This document is not contractual and the equipment specification may be modified at any time without prior notice.

