

# Integrated LED Emergency Downlight

- ★ Cost effective
- ★ 50,000 hours lifespan with 5 years warranty
- ★ Visible at long distance
- ★ Quality driver and battery
- ★ Uniform and High lumen output
- ★ Easy installation



## BSTALONEEM1

General Specification		PART No. BSTALONEEM1	
Product Dimension	206*150*55mm	Version	Non-Maintained
Finish/Color	White	Packing Method	Brown box
IP Rating	IP20	Energy Rating	D
Dimmable (Yes/No)	No	Warranty	5 years, 2 years (Battery)
Light Source Specification		Electrical Specification	
CCT (K)	6500K	Input Voltage	180-240V AC 50/60Hz
Lumens Per Watt	130lm (max)	Power	1W
Lumen output	130lm (open) 120lm (corridor)	Battery	LiFePO4
CRI (Ra)	80	Emergency time	3 hours
Lifetime	50000hrs	Elec. Classification	Class II
Beam Angle	150°(open) 65°x160°(corridor)	Control gear spec	Constant current
SMD quantity	1 pc		
Packing Specification			
Box Dimensions	250*150*60mm	Carton Dimensions	590*160*260mm
QTY/CTN	9	Weight	3kg
Installation			
Fixing Method	Recessed mounting	Ambient Temp	0 °C - 40 °C

This document is not contractual and the equipment specification may be modified at any time without prior notice.

