

Integrated LED Emergency Downlight

- ★ Cost effective
- ★ 50,000 hours lifespan with 5 years warranty
- ★ Visible at long distance
- ★ Quality driver and battery
- ★ Uniform and High lumen output
- ★ Easy installation



General Specification		PART No. BSTALONEEM	
Product Dimension	40*40*20mm	Version	Non-Maintained
Finish/Color	White	Packing Method	Color box
IP Rating	IP20	Energy Rating	A++
Dimmable (Yes/No)	No	Warranty	5 years
Light Source Specification		Electrical Specification	
CCT (K)	6000K	Input Voltage	180-240V AC 50/60Hz
Lumens Per Watt	80	Power	2W
Lumen output	160	Battery	LiFePO4
CRI (Ra)	80	Emergency time	3-4 hours
Lifetime	50000hrs	Elec. Classification	Class II
Beam Angle	120°	Control gear spec	Constant current
SMD quantity	1 pc		
Packing Specification			
Box Dimensions	180x60x53mm	Carton Dimensions	36.5X27.5X25.5cm
QTY/CTN	40	Weight	8kg
Installation			
Fixing Method	Recessed mounting	Ambient Temp	0 °C - 30 °C

This document is not contractual and the equipment specification may be modified at any time without prior notice.

